

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

MPSA12
MPSA13
MPSA14
NPN SILICON DARLINGTON TRANSISTOR
JEDEC TO-92 CASE (EBC)

DESCRIPTION

The CENTRAL SEMICONDUCTOR MPSA12 Series types are epoxy molded Silicon NPN Epitaxial Planar Darlington Transistors designed for applications requiring extremely high gain.

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL	MPSA12	MPSA13	MPSA14	UNIT
Collector Base Voltage	V_{CB0}	-	30	30	V
Collector Emitter Voltage	V_{CES}	20	30	30	V
Emitter Base Voltage	V_{EBO}	10	10	10	V
Collector Current	I_C		500		mA
Power Dissipation	P_D		625		mW
Power Dissipation ($T_C=25^\circ\text{C}$)	P_D		1.5		W
Operating and Storage Junction Temperature	T_J, T_{stg}		-65 TO +150		$^\circ\text{C}$
Thermal Resistance	θ_{JA}		0.2		$^\circ\text{C}/\text{mW}$
Thermal Resistance	θ_{JC}		83.3		$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MPSA12		MPSA13		MPSA14		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
I_{CB0}	$V_{CB}=15\text{V}$		100		-		-	nA
I_{CB0}	$V_{CB}=30\text{V}$		-		100		100	nA
I_{CES}	$V_{CE}=15\text{V}$		100		-		-	nA
I_{EBO}	$V_{EB}=10\text{V}$		100		100		100	nA
BV_{CES}	$I_C=100\mu\text{A}$	20		30		30		V
$V_{CE(SAT)}$	$I_C=10\text{mA}, I_B=10\mu\text{A}$		1.0		-		-	V
$V_{CE(SAT)}$	$I_C=100\text{mA}, I_B=100\mu\text{A}$		-		1.5		1.5	V
$V_{BE(ON)}$	$V_{CE}=5.0\text{V}, I_C=10\text{mA}$		1.4		-		-	V
$V_{BE(ON)}$	$V_{CE}=5.0\text{V}, I_C=100\text{mA}$		-		2.0		2.0	V
h_{FE}	$V_{CE}=5.0\text{V}, I_C=10\text{mA}$	20,000		5,000		10,000		
h_{FE}	$V_{CE}=5.0\text{V}, I_C=100\text{mA}$	-		10,000		20,000		
f_T	$V_{CE}=5.0\text{V}, I_C=10\text{mA}, f=100\text{MHz}$	-		125		125		MHz